


SPD SERIES Surge Protective Device

DL-B10S/B10P-SPD Specification V1.1

Features

- Meet the safety and performance tests of Class II or Class III.
- Protection mode: L-N. L-PE. N-PE.
- Built in thermal separation function, higher safety.
- Parallel and series connection mode optional , with its own lead.
- Excellent surge impact resistance and low residual voltage.
- Miniature size and convenient for embedded installation.
- IP67 Water-proof and Dust-proof.



Applications

Street lighting、Digital signage、Tunnel lighting、Gas station lighting
Stadium lighting、Traffic lighting、Port lighting、Industrial lighting



Description

DL-SPD series thermally protected Surge Protective Device is specially designed to be used in outdoor and commercial LED lighting fixtures for transient over voltage protection. It is mainly composed of thermally protected varistors and gas discharge tube components. Its built-in thermal disconnect function provides additional protection to prevent catastrophic failure and fire hazard even under the extreme circumstances of varistor end-of-life or sustaining over voltage conditions. The product is connected with LED power driver to provide reliable lighting surge protection, which can effectively prolong the service life and stability of luminaires.


Model list

Model NO.	Input voltage	Protection voltage	Remark
DL-B10P-SPD	100-277V	10KV	Parallels connection
DL-B10S-SPD	100-277V	10KV	Series connection


Electrical Data

Product model	DL-B10P-SPD	DL-B10S-SPD
Standards	EN 61643-11、IEC 61643-11	EN 61643-11、IEC 61643-11
Nominal operating voltage/Un	100- 277V (50/60Hz)	100- 277V (50/60Hz)
Max. continuous operating voltage/MCOV (Uc)	320V (50/ 60Hz)	320V (50/ 60Hz)
Rated load current/IL	-	8A
Nominal discharge current/I.(8/20us)	5kA	5kA
Max. discharge current/Im»(8/20us)	10kA	10kA
Open-circuit voltage/Uc(1.2/50us&8/20us)	10kV	10kV
Voltage protection level/Up(@In)	Clamping Voltage≤1. 5kV(L-N.L/N-PE) Peak Voltage≤1. 8kV(L-N.L/N-PE)	Clamping Voltage≤1. 5kV(L-N.L/N-PE) Peak Voltage≤1. 8kV(L-N.L/N-PE)
Operating state/fault indication	on normally, off fault	on normally, off fault
Connecting wires	06 (RV) 1.0mm²	06 (RV) 1.0mm²
Connection mode	Parallel connection	Series connection
Operating temperature range	-40C~+85°C	-40C~+85°C
Degree of protection	IP67	IP67


Repetitive surge capability



Test waveform





Lightning surge test (8/20us)	
Surge	Strikes
10000A	1
7000A	2
5000A	15



Lightning surge test (8/20us&1.2/50us)	
Surge	Strikes
5KA/10KV	120

Application / Installation schematic




Warning: The phase line and neutral line of the SPD shall not be reversed. and the ground wire shall be reliably grounded.

Mechanical specification

Size (mm)	L60*W34*H20
-------------	-------------

DL-B10S/B10P-SPD




Weight

Weight	60 g
--------	------

Packaging

Packaging (mm) L405 *W400*H230



Note: One Carton 2 layers and 150 pcs each layer, total 300pcs/carton.

Version

DATE	DESCRIPTION	REV.	CHECK
2025.3.26	Initial version.	V1.0	
2025.5.19	Modify the devices for the applicable lamps	V1.1	JH 2025.05.20 14:24:12 +08'00' DYX 2025.05.20 15:00:47 +08'00'

MANUFACTRUER

EDIT	CHECK	APPROVE
周敏慧 ZMH 2025.05.19 15:12:26 +08'00' 李志平 LZP 2025.05.20 11:24:29 +08'00'	梁庆能 LQN 2025.05.20 11:32:37 +08'00'	张鸿生 数字签名者：张鸿生 DN：cn=张鸿生,o,ou, email=978425630@qq.co m,c=<无 日期：2025.05.20 15:39:02 +08'00'